

Video Borescope/Camera Tester

- ✓ **17mm camera diameter and 2.4" Color TFT LCD Monitor**
also tests installed surveillance cameras for correct target alignment



Features:

- 17mm diameter camera head with 39" (1m) flexible gooseneck cable retains configured shape
- Mini water-proof (IP57) camera head for high resolution viewing
- Four LED lamps with five brightness levels illuminate the viewed object
- Glare-free close-up field of view with 480 x 234 pixel display
- Automatically detects NTSC and PAL cameras
- Switches to standby mode when no input is connected
- Battery can be recharged via the built-in USB port using the included AC adaptor/charger or a USB port on your PC
- Complete with rechargeable Lithium battery, and Universal AC adapter/charger with USB cable

Applications:

- Home inspection: Inspect in walls for mold, insect infestation, electrical wire or water pipe location
- HVAC: Inspect inside ducts, behind motors and compressors
- Automotive: View inside or around engines and transmissions
- Government: Safety and security inspections
- Industrial: Inspect weld integrity, process equipment, gears, molding machines
- Aerospace: Aircraft inspections for contamination, debris, cracks or other damage

Ordering Information:

BR50Video Borescope/Camera Tester
BRC-17CAMReplacement 17mm Camera tip with cable

